


BASIC Stamp II



Thank you for purchasing the BASIC Stamp Programming Package.

This is the manual for our new BASIC Stamp II module (shown above). Everything you need to know about programming the Stamp II may be found in this manual. However, even if you're only interested in the Stamp II, you may gain useful knowledge by referring to the Stamp I manual. The Stamp I manual has a collection of interesting application notes, which may only need slight modification to run on the Stamp II.

If you have any questions, please let us know.

BLANK PAGE

BASIC Stamp II

| | |
|--|-----------|
| Hardware Setup | 5 |
| System Requirements | 5 |
| Packing List | 5 |
| Connecting to the PC | 6 |
| Carrier Board Features | 6 |
| BS2-IC Pinout | 7 |
| Using the Editor | 8 |
| Starting the Editor | 8 |
| Entering & Editing Programs | 9 |
| Editor Function Keys | 9 |
| BASIC Instruction Summary | 11 |
| Programming the Stamp II | 14 |
| Program and Data Memory | 14 |
| Defining variables (VAR) | 17 |
| Defining constants (CON) | 20 |
| Defining data (DATA) | 21 |
| Run-time expressions | 23 |
| BASIC Instructions | 27 |
| BRANCH | 27 |
| BUTTON | 28 |
| COUNT | 29 |
| DEBUG | 30 |
| DTMFOUT | 32 |
| END | 33 |
| FOR...NEXT | 34 |
| FREQOUT | 35 |
| GOSUB | 36 |
| GOTO | 37 |
| HIGH | 38 |
| IF...THEN | 39 |
| INPUT | 40 |
| LOOKDOWN | 41 |
| LOOKUP | 42 |
| LOW | 43 |
| NAP | 44 |
| OUTPUT | 45 |
| PAUSE | 46 |
| PULSIN | 47 |
| PULSOUT | 48 |
| PWM | 49 |

BASIC Stamp II

| | |
|--|-----------|
| RANDOM | 50 |
| RCTIME | 51 |
| READ | 52 |
| RETURN | 53 |
| REVERSE | 54 |
| SERIN | 55 |
| SEROUT | 59 |
| SHIFTIN | 62 |
| SHIFTOUT | 63 |
| SLEEP | 64 |
| STOP | 65 |
| TOGGLE | 66 |
| WRITE | 67 |
| XOUT | 68 |
| Stamp II Application Notes | 69 |
| Note 1: Controlling lights and appliances with X-10 (XOUT) | 69 |
| Note 2: Using SHIFTIN and SHIFTOUT | 75 |

BASIC Stamp II

System Requirements

To program Stamp IIs, you'll need the following computer system:

- IBM PC or compatible computer
- 3.5-inch disk drive
- Serial port
- 128K of RAM
- MS-DOS 2.0 or greater

To power the Stamps, you can use a 9-volt battery (this is the most convenient method). You can also use a 5-15 volt power supply, but you should be careful to connect the supply to the appropriate part of the Stamp. A 5-volt supply should be connected directly to the Stamp's +5V pin (also called VDD), but a higher voltage should be connected to the Stamp's PWR pin (also called VIN).

Connecting a high voltage supply (greater than 6 volts) to the 5-volt pin can permanently damage the Stamp.

Packing List

If you purchased the Stamp Programming Package, you should have received the following items:

- Stamp I programming cable (parallel port DB25-to-3 pin)
- Stamp I manual
- Stamp I application notes (contained in Stamp I manual)

- Stamp II programming cable (serial port DB9-to-DB9)
- Stamp II manual (this booklet)

- 3.5-inch diskette

If any items are missing, please let us know.


BASIC Stamp II

Connecting to the PC


To program a Stamp II, you'll need to connect it to your PC and then run the editor/downloader software. In this booklet, it's assumed that you have a BS2-IC and its corresponding carrier board (shown below).

To connect the Stamp II to your PC, follow these steps:

- 1) Plug the BS2-IC onto the carrier board. The BS2-IC plugs into a 24-pin DIP socket, located in the center of the carrier. When plugged onto the carrier board, the words "Parallax BS2-IC" should be near the reset button.
- 2) In the Stamp Programming Package, you received a serial cable to connect the Stamp II to your PC. Plug the female end into an available serial port on your PC.
- 3) Plug the male end of the serial cable into the carrier board's serial port.
- 4) Supply power to the carrier board, either by connecting a 9-volt battery or by providing an external power source.



BASIC Stamp II



| Pin | Name | Description | Comments |
|-----|---------------|-------------------|--|
| 1 | TX | Serial output | Connect to pin 2 of PC serial DB9 (RX) * |
| 2 | RX | Serial input | Connect to pin 3 of PC serial DB9 (TX) * |
| 3 | ATN | Active-high reset | Connect to pin 4 of PC serial DB9 (DTR) * |
| 4 | GND | Serial ground | Connect to pin 5 of PC serial DB9 (GND) * |
| 5 | P0 | I/O pin 0 | Each pin can source 20 ma and sink 25 ma. P0-P7 and P8-P15, as groups, can each source a total of 40 ma and sink 50 ma. |
| 6 | P1 | I/O pin 1 | |
| 7 | P2 | I/O pin 2 | |
| 8 | P3 | I/O pin 3 | |
| 9 | P4 | I/O pin 4 | |
| 10 | P5 | I/O pin 5 | |
| 11 | P6 | I/O pin 6 | |
| 12 | P7 | I/O pin 7 | |
| 13 | P8 | I/O pin 8 | |
| 14 | P9 | I/O pin 9 | |
| 15 | P10 | I/O pin 10 | |
| 16 | P11 | I/O pin 11 | |
| 17 | P12 | I/O pin 12 | |
| 18 | P13 | I/O pin 13 | |
| 19 | P14 | I/O pin 14 | |
| 20 | P15 | I/O pin 15 | |
| 21 | <u>+5V</u> ** | +5V supply | 5-volt input or regulated output. |
| 22 | RES | Active-low reset | Pull low to reset; goes low during reset. |
| 23 | GND | System ground | |
| 24 | PWR ** | Regulator input | Voltage regulator input; takes 5-15 volts. |

* For automatic serial port selection by the Stamp II software, there must also be a connection from DSR (DB9 pin 6) to RTS (DB9 pin 7). This connection is made on the Stamp II carrier board. If you are not using the carrier board, then you must make this connection yourself, or use the command-line option to tell the software which serial port to use.

** During normal operation, the Stamp II takes about 7 mA. In various power-down modes, consumption can be reduced to about 50 μ A.

BASIC Stamp II

Starting the Editor

With the Stamp II connected and powered, insert the BASIC Stamp diskette and then enter the Stamp II directory by typing the following command from the DOS prompt:

```
CD STAMP2
```

Once in the Stamp II directory, you can run the Stamp II editor/downloader software by typing the following command:

```
STAMP2
```

The Stamp II software will start running after several seconds. The editor screen is dark blue, with one line across the top that indicates how to get on-screen editor help. Except for the top line, the entire screen is available for entering and editing BASIC programs.

Command-line options:

There are several command-line options that may be useful when running the software; these options are shown below:

- | | |
|------------------------------|---|
| <code>STAMP2 filename</code> | Runs the editor and loads <i>filename</i> . |
| <code>STAMP2 /m</code> | Runs the editor in monochrome mode. May give a better display on some systems, especially laptop computers. |
| <code>STAMP2 /n</code> | Runs the editor and specifies which serial port to use when downloading to the Stamp II (note that <i>n</i> must be replaced with a serial port number of 1-4). |

Normally, the software finds the Stamp II by looking on all serial ports for a connection between DSR and RTS (this connection is made on the carrier board). If the DSR-RTS connection is not present, then you must tell the software which port to use, as shown above.

BASIC Stamp II

Entering & Editing Programs

We've tried to make the editor as intuitive as possible: to move up, press the *up arrow*; to highlight one character to the right, press *shift-right arrow*; etc.

Most functions of the editor are easy to use. Using single keystrokes, you can perform the following common functions:

- Load, save, and run programs.
- Move the cursor in increments of one character, one word, one line, one screen, or to the beginning or end of a file.
- Highlight text in blocks of one character, one word, one line, one screen, or to the beginning or end of a file.
- Cut, copy, and paste highlighted text.
- Search for and/or replace text.
- See how the Stamp IIs memory is being used by your program.
- Identify the version of the BASIC interpreter in your Stamp II.

Editor Function Keys

The following list shows the keys that are used to perform various functions:

| | |
|-------|--|
| F1 | Display editor help screen. |
| Alt-R | Run program in Stamp II (<i>download the program on the screen, then run it</i>) |
| Alt-L | Load program from disk |
| Alt-S | Save program on disk |
| Alt-M | Show memory usage maps |
| Alt-I | Show version number of BASIC interpreter |
| Alt-Q | Quit editor and return to DOS |
| Enter | Enter information and move down one line |
| Tab | Same as Enter |

BASIC Stamp II

| | |
|----------------------|---|
| Left arrow | Move left one character |
| Right arrow | Move right one character |
| Up arrow | Move up one line |
| Down arrow | Move down one line |
| Ctrl-Left | Move left to next word |
| Ctrl-Right | Move right to next word |
| Home | Move to beginning of line |
| End | Move to end of line |
| Page Up | Move up one screen |
| Page Down | Move down one screen |
| Ctrl-Page Up | Move to beginning of file |
| Ctrl-Page Down | Move to end of file |
| Shift-Left | Highlight one character to the left |
| Shift-Right | Highlight one character to the right |
| Shift-Up | Highlight one line up |
| Shift-Down | Highlight one line down |
| Shift-Ctrl-Left | Highlight one word to the left |
| Shift-Ctrl-Right | Highlight one word to the right |
| Shift-Home | Highlight to beginning of line |
| Shift-End | Highlight to end of line |
| Shift-Page Up | Highlight one screen up |
| Shift-Page Down | Highlight one screen down |
| Shift-Ctrl-Page Up | Highlight to beginning of file |
| Shift-Ctrl-Page Down | Highlight to end of file |
| Shift-Insert | Highlight word at cursor |
| ESC | Cancel highlighted text |
| Backspace | Delete one character to the left |
| Delete | Delete character at cursor |
| Shift-Backspace | Delete from left character to beginning of line |
| Shift-Delete | Delete to end of line |
| Ctrl-Backspace | Delete line |
| Alt-X | Cut marked text and place in clipboard |
| Alt-C | Copy marked text to clipboard |
| Alt-V | Paste (insert) clipboard text at cursor |
| Alt-F | Find string (establish search information) |
| Alt-N | Find next occurrence of string |

BASIC Stamp II

The following list is a summary of the BASIC instructions used by the BASIC Stamp II. Later in this pamphlet, you'll find complete descriptions of each instruction.

- ◆ This symbol indicates new or greatly improved instructions (compared to the BASIC Stamp I).

BRANCHING

| | |
|-----------|--|
| IF...THEN | Compare and conditionally branch. |
| BRANCH | Branch to address specified by offset. |
| GOTO | Branch to address. |
| GOSUB | Branch to subroutine at address. GOSUBs may be nested up to four levels deep, and you may have up to 255 GOSUBs in your program. |
| RETURN | Return from subroutine. |

LOOPING

| | |
|------------|----------------------------|
| FOR...NEXT | Establish a FOR-NEXT loop. |
|------------|----------------------------|

NUMERICS

| | |
|----------|--|
| LOOKUP | Lookup data specified by offset and store in variable. This instruction provides a means to make a lookup table. |
| LOOKDOWN | Find target's match number (0-N) and store in variable. |
| RANDOM | Generate a pseudo-random number. |

DIGITAL I/O

| | |
|---------|---|
| INPUT | Make pin an input |
| OUTPUT | Make pin an output. |
| REVERSE | If pin is an output, make it an input. If pin is an input, make it an output. |
| LOW | Make pin output low. |
| HIGH | Make pin output high. |
| TOGGLE | Make pin an output and toggle state. |
| PULSIN | Measure an input pulse (resolution of 2 μ s). |

BASIC Stamp II

PULSOUT Output a timed pulse by inverting a pin for some time (resolution of 2 μ s).

BUTTON Debounce button, perform auto-repeat, and branch to address if button is in target state.

- ◆ **SHIFIN** Shift bits in from parallel-to-serial shift register.
- ◆ **SHIFOUT** Shift bits out to serial-to-parallel shift register.
- ◆ **COUNT** Count cycles on a pin for a given amount of time (0 - 125 kHz, assuming a 50/50 duty cycle).
- ◆ **XOUT** Generate X-10 powerline control codes. For use with TW523 or TW513 powerline interface module.

SERIAL I/O

- ◆ **SERIN** Serial input with optional qualifiers, time-out, and flow control. If qualifiers are given, then the instruction will wait until they are received before filling variables or continuing to the next instruction. If a time-out value is given, then the instruction will abort after receiving nothing for a given amount of time. Baud rates of 300 - 50,000 are possible (0 - 19,200 with flow control). Data received must be N81 (no parity, 8 data bits, 1 stop bit) or E71 (even parity, 7 data bits, 1 stop bit).
- ◆ **SEROUT** Send data serially with optional byte pacing and flow control. If a pace value is given, then the instruction will insert a specified delay between each byte sent (pacing is not available with flow control). Baud rates of 300 - 50,000 are possible (0 - 19,200 with flow control). Data is sent as N81 (no parity, 8 data bits, 1 stop bit) or E71 (even parity, 7 data bits, 1 stop bit).

ANALOG I/O

PWM Output PWM, then return pin to input. This can be used to output analog voltages (0-5V) using a capacitor and resistor.

- ◆ **RCTIME** Measure an RC charge/discharge time. Can be used to measure potentiometers.

BASIC Stamp II

SOUND

- ◆ **FREQOUT** Generate one or two sinewaves of specified frequencies (each from 0 - 32767 Hz.).
- ◆ **DTMFOUT** Generate DTMF telephone tones.

EEPROM ACCESS

- ◆ **DATA** Store data in EEPROM before downloading BASIC program.
- READ** Read EEPROM byte into variable.
- WRITE** Write byte into EEPROM.

TIME

- PAUSE** Pause execution for 0–65535 milliseconds.

POWER CONTROL

- NAP** Nap for a short period. Power consumption is reduced.
- SLEEP** Sleep for 1–65535 seconds. Power consumption is reduced to approximately 50 μ A.
- END** Sleep until the power cycles or the PC connects. Power consumption is reduced to approximately 50 μ A.

PROGRAM DEBUGGING

- DEBUG** Send variables to PC for viewing.

BASIC Stamp II


Program and Data Memory

The BS2 has 2K bytes of EEPROM which holds the executable BASIC program and any data. Memory not used by the BASIC program can be read and written at run-time as a data bank, or initialized with data at download time. This memory is only affected by downloading or run-time modification.

There are 32 bytes of RAM which serve as variable space and I/O pin interface for the BASIC program. This memory can be accessed as words, bytes, nibbles, or bits. Each time the BASIC program is run anew, this memory is cleared to all zeroes.

So, the 2K byte EEPROM is for program and data, and only affected by initial downloading or run-time modification. It survives power-down. The 32 bytes of RAM are for run-time variables and I/O pin access. This memory is cleared each time the BS2 is powered up, reset, or downloaded to.

The 2K-byte EEPROM is arranged as follows:



BASIC Stamp II

The 32-byte RAM is arranged as follows:

| Word | Bits | Description | R/W |
|------|---------------------|--------------------|------------|
| \$0 | 0000 0000 0000 0000 | Pin input states | read-only |
| \$1 | 0000 0000 0000 0000 | Pin output latches | read/write |
| \$2 | 0000 0000 0000 0000 | Pin directions | read/write |
| \$3 | 0000 0000 0000 0000 | variable space | read/write |
| \$4 | 0000 0000 0000 0000 | variable space | read/write |
| \$5 | 0000 0000 0000 0000 | variable space | read/write |
| \$6 | 0000 0000 0000 0000 | variable space | read/write |
| \$7 | 0000 0000 0000 0000 | variable space | read/write |
| \$8 | 0000 0000 0000 0000 | variable space | read/write |
| \$9 | 0000 0000 0000 0000 | variable space | read/write |
| \$A | 0000 0000 0000 0000 | variable space | read/write |
| \$B | 0000 0000 0000 0000 | variable space | read/write |
| \$C | 0000 0000 0000 0000 | variable space | read/write |
| \$D | 0000 0000 0000 0000 | variable space | read/write |
| \$E | 0000 0000 0000 0000 | variable space | read/write |
| \$F | 0000 0000 0000 0000 | variable space | read/write |

Word \$0 always reflects the read-state of all 16 I/O pins. Whether a pin is an input or output, it's logical state can be read in this word. Word \$0 is accessed by the following symbolic names:

| | |
|------|--|
| INS | the entire 16-bit word |
| INL | the low byte of INS |
| INH | the high byte of INS |
| INA | the low nibble of INL |
| INB | the high nibble of INL |
| INC | the low nibble of INH |
| IND | the high nibble of INH |
| INO | the low bit of INS (corresponds to I/O pin P0) |
| IN15 | the high bit of INS (corresponds to I/O pin P15) |

BASIC Stamp II

Word \$1 contains the output latches for all 16 I/O pins. If a pin is in input mode, this data is unused; but, when a pin is in output mode, its corresponding word \$1 bit sets its state. The bits are all readable and writable, regardless of pin direction. These are its symbolic names:

OUTS the entire 16-bit word

OUTL the low byte of OUTS

OUTH the high byte of OUTS

OUTA the low nibble of OUTL

OUTB the high nibble of OUTL

OUTC the low nibble of OUTH

OUTD the high nibble of OUTH

OUT0 the low bit of OUTS - corresponds to pin P0

OUT15 the high bit of OUTS - corresponds to pin p15

Word \$2 contains the direction bits for all 16 I/O pins. To place a pin in input mode, its corresponding word \$2 bit must be cleared to 0. To place a pin into output mode, its corresponding word \$2 bit must be set to 1, at which time its word \$1 bit will determine whether it drives high or low. Word \$2 has these symbolic names:

DIRS the entire 16-bit word

DIRL the low byte of DIRS

DIRH the high byte of DIRS

DIRA the low nibble of DIRL

DIRB the high nibble of DIRL

DIRC the low nibble of DIRH

DIRD the high nibble of DIRH

DIR0 the low bit of DIRS - corresponds to pin P0

DIR15 the high bit of DIRS - corresponds to pin p15

BASIC Stamp II

Words \$3-\$F are for general purpose variable use and have no pre-assigned symbolic names. The VAR statement is used to allocate this memory.

The above text introduced the physical pin-out of the BASIC Stamp II, as well as the internal EEPROM, RAM, and I/O structure. The following text discusses the programming of the BS2.

Programming the BASIC Stamp II

In the BASIC Stamp II, there are two general categories of BASIC statements: compile-time and run-time.

Compile-time statements are resolved when you compile the program (Alt-R or Alt-M), and they do not generate any executable code.

Run-time statements generate code and are executed at run-time.

There are three compile-time statements. They are used for declaring variables, constants, and data. They are:

VAR, CON, and DATA

The VAR statement - defining variables

Your program should begin with a declaration of all of its variables. VAR statements assign symbolic names to variable RAM (RAM not used by I/O - words \$3-\$F). This is done as follows:

'Declare the variables

| | | | |
|-------|-----|---------|---------------------------------------|
| cat | var | nib | 'make "cat" a nibble variable |
| mouse | var | bit | 'make "mouse" a bit variable |
| dog | var | byte | 'make "dog" a byte variable |
| rhino | var | word | 'make "rhino" a word variable |
| snake | var | bit(10) | 'make "snake" a 10-piece bit variable |

BASIC Stamp II

The compiler will group all words, bytes, nibs, and bits, and respectively arrange them into unused RAM. By pressing Alt-M, you can see a picture of the RAM allocation. First, the three I/O words are shown, then all words, bytes, nibs, and finally, bits, are seen. Empty RAM follows. Alt-M is a quick way to assess how much RAM you've used.

The VAR usage options are as follows:

'define unique variables

| | | | |
|------|-----|------|-------------------------|
| sym1 | VAR | bit | 'make a bit variable |
| sym2 | VAR | nib | 'make a nibble variable |
| sym3 | VAR | byte | 'make a byte variable |
| sym4 | VAR | word | 'make a word variable |

'After bit/nib/byte/word a value may be placed
'within parentheses to declare an array size:

| | | | |
|------|-----|----------|-------------------------|
| sym5 | VAR | nib (10) | 'make a 10 nibble array |
|------|-----|----------|-------------------------|

'define variables-within-variables or alias variables

| | | | |
|------|-----|--------------|--|
| sym6 | VAR | sym4.highbit | 'make a bit variable of sym4's highbit |
| sym7 | VAR | sym4.lowbit | 'make a bit variable of sym4's lowbit |
| sym8 | VAR | sym2 | 'make an alternate name for sym2 |

'When using VAR to assign non-unique variables (a variable
'name is used in lieu of bit/nib/byte/word(size)), a period may
'be placed after the variable name and followed by modifiers.
'Modifiers are used to identify sub-pieces of the initially-
'mentioned variable.

| | | | |
|------|-----|---------------------------|------------------|
| sym9 | VAR | sym4.highbyte.lownib.bit2 | 'picky, picky... |
|------|-----|---------------------------|------------------|

Here are all the variable modifiers:

| | |
|----------|------------------------------|
| LOWBYTE | 'low byte of a word |
| HIGHBYTE | 'high byte of a word |
| BYTE0 | 'byte0 (low byte) of a word |
| BYTE1 | 'byte1 (high byte) of a word |

BASIC Stamp II

| | |
|---------|--------------------------------------|
| LOWNIB | 'low nibble of a word or byte |
| HIGHNIB | 'high nibble of a word or byte |
| NIB0 | 'nib0 of a word or byte |
| NIB1 | 'nib1 of a word or byte |
| NIB2 | 'nib2 of a word |
| NIB3 | 'nib3 of a word |
| LOWBIT | 'low bit of a word, byte, or nibble |
| HIGHBIT | 'high bit of a word, byte, or nibble |
| BIT0 | 'bit0 of a word, byte, or nibble |
| BIT1 | 'bit1 of a word, byte, or nibble |
| BIT2 | 'bit2 of a word, byte, or nibble |
| BIT3 | 'bit3 of a word, byte, or nibble |
| BIT4 | 'bit4 of a word or byte |
| BIT5 | 'bit5 of a word or byte |
| BIT6 | 'bit6 of a word or byte |
| BIT7 | 'bit7 of a word or byte |
| BIT8 | 'bit8 of a word |
| BIT9 | 'bit9 of a word |
| BIT10 | 'bit10 of a word |
| BIT11 | 'bit11 of a word |
| BIT12 | 'bit12 of a word |
| BIT13 | 'bit13 of a word |
| BIT14 | 'bit14 of a word |
| BIT15 | 'bit15 of a word |

In summary, to declare variables, VAR statements are used. VAR statements either declare unique variables or variables-within-variables and alias-variables.

For defining unique variables:

symbol VAR size (array)

- *symbol is a unique name for a variable*
- *size is either WORD, BYTE, NIB, or BIT*
- *(array) is an optional expression which declares an array size*

For defining variables-within-variables or alias-variables:

BASIC Stamp II

symbol VAR variable.modifiers

- *symbol is a unique name for a variable*
- *variable is a defined variable name*
- *.modifiers are optional and used to define variables-within-variables*

The compiler will group all declarations by size (in the case of unique variables) and assign them to unused RAM. Alt-M lets you see the result of this process. Non-unique variables are in-whole or in-part derived from unique variables and get assigned within the unique-variable memory.

Keep in mind that you may make alias names for the pin variables:

keyin var in5 'make "keyin" a way to read P5's state.

Note for Stamp I users: *W0-W12 (and the corresponding B0-B25) are pre-defined by the compiler software to make use of Stamp I programs easier. If you use a Stamp I program with the Stamp II, you can enter the older "Wx" and "Bx" variable names without having to define them first.*

The CON statment - defining constants

The CON statement is similar to the VAR statement, except that it is for defining constant values and assigning them to symbolic names. This is handy for having a single declaration which gets accessed throughout your program. The CON syntax is as follows:

symbol CON expression 'assign expression to "symbol"

- *symbol is a unique symbolic name for a constant*
- *expression is a compile-time-resolvable constant*

level CON 10 "level" is same as 10 in program
limit CON 10*4<<2 "limit" is 160

expressions after CON can contain the following binary operators and are resolved left-to-right:

BASIC Stamp II

+ add
- subtract
* multiply
/ divide
<< shift left
>> shift right
& logical AND
| logical OR
^ logical XOR

example:

```
growth   CON 100-light/gel  "light" and "gel" are CON's, too
```

The DATA statement - defining data

EEPROM memory not used by your BASIC program can be used for data storage. Keep in mind that your BASIC program builds from the end of memory towards the start of memory. This allocation is automatic. Your data, on the other hand, builds from the start of memory towards the end. The sum of program and data memory cannot exceed the 2K byte limit. The compiler will always tell you when you have a conflict.

DATA statements are used to build data into unused memory. Initially, the DATA location is set to 0. It is advanced by 1 for each byte declared. Here is an example DATA statement:

```
table DATA "Here is a string..."
```

Usually, you'll want to precede DATA statements with a unique symbol. The symbol will be assigned a constant value (as if via CON) which is the current data pointer. The text following 'DATA' is usually a list of bytes which can be constant expressions. In the above example (assuming this was the first DATA statement in the program), "table" becomes a constant symbol of value 0; "Here is a string..." is broken into individual bytes and placed into EEPROM memory sequentially. Alt-M and two <SPACE>s will show you the result of this line.

BASIC Stamp II

The DATA pointer may be altered at any time by an @ sign followed by a new pointer value:

```
list DATA @$100,"some data"
```

DATA has a few variations of use to allocate defined and undefined data. Defined data is fully declared and known at compile time. Undefined data is the mere allocation of data space, while not assigning values into the bytes of EEPROM (to be done at run-time, instead). Defined and undefined data are declared as follows:

for defined data:

```
fee DATA 0,1,2,3,4,5,6,7,8,9 'actual bytes
fie DATA word 1000 'make two bytes: $E8 and $03
foe DATA 0 (256) '256 bytes initialized as 0
```

for undefined data:

```
fum DATA (1024) 'reserved 1K byte of undefined data
abc DATA word (16) 'reserve 16 words of undefined data
```

Important concept: Defined DATA and BASIC program memory are always downloaded to the BS2. Undefined data and unused EEPROM memory are not downloaded. This allows you to change programs while keeping data, assuming both programs defined the same stretch of memory as undefined DATA. Alt-M will show you maps of EEPROM allocation. This download/don't-download rule is applied to 16-byte blocks. If any byte within a 16-byte block is defined DATA or BASIC program, that whole block is downloaded. Use Alt-M to see this.

In summary, DATA is used to define EEPROM byte usage that doesn't conflict with the BASIC program storage:

- DATA can be preceded by a symbol which will be assigned the constant value of the current DATA pointer.
- Byte-size data is assumed, but 'word' can be used to break a word into two bytes of storage.
- The @ sign is used to redirect the DATA pointer. If a symbol precedes

BASIC Stamp II

a DATA statement and the first thing after DATA is @, the new pointer value is assigned to the symbol.

- Defined data is spelled out, so to speak, with numbers and letters.
- Defined data may be repeated at the byte or word level using (array).
- Undefined data may be reserved by using (array) unpreceded by a value.

Note: DATA can contain references to DATA symbols:

```
t1    DATA    "Here's table 1..." ,0
t2    DATA    "Here's table 2..." ,0
t3    DATA    "Here's table 3..." ,0
t4    DATA    "Here's table 4..." ,0

start DATA    word t1, word t2, word t3, word t4
```

Run-Time Expressions

Run-time expressions can contain constants, variables, operators, and parentheses. They are resolved using 16-bit math.

Constants can be in several forms:

| | |
|------------|---|
| label | A label may be assigned a constant via CON. |
| \$BA1F | Hex |
| %111001111 | Binary |
| 99 | Decimal |
| "A" | ASCII |

Note: When more than one character is within quotes, they are separated by the compiler as such: "DOG" becomes "D", "O", "G". "String"+\$80 becomes: "S", "t", "r", "i", "n", "g"+\$80.

Variables can be accessed a number of ways:

| | |
|-----------------|--|
| somevar | Some variable. |
| wordvar.highbit | Use modifiers to access sub-variables. |

BASIC Stamp II

| | |
|----------------------|--|
| nibarray(index) | A variable followed by an expression in quotes is indexed as an array (0=1st element). |
| word.bit0(bitoffset) | Scan a word, one bit at a time. |

If a variable were defined as:

string var byte (10)

It could be accessed as:

| | |
|-------------------------|------------------------|
| string | The 1st byte |
| string (0) | The 1st byte |
| string (1) | The 2nd byte |
| string (9) | The 10th (last) byte |
| string.lownib(nibindex) | Nibindex could be 0-19 |
| string.lowbit(bitindex) | Bitindex could be 0-79 |

There are also binary, unary, and conditional expression operators.

Unary operators precede a variable or constant or (expression) and have highest priority. They are as follows:

| | |
|-----|---|
| SQR | Square root of unsigned 16-bit value |
| ABS | Absolute of signed 16-bit value |
| ~ | One's complement of 16-bit value (bitwise not) |
| - | Two's complement of 16-bit value (negation) |
| DCD | 2 ⁿ decoder of 4-bit value (0...15 -> 1,2,4,8,16,...32768) |
| NCD | Priority encoder of 16-bit value (=>32768,=>16384,=>8192,...=1 -> 15,14,13,...1 ; 0 -> \$FFFF) |
| COS | Cosine of 8-bit value. Result is in the range of +-127, unit circle is 0-255 radial units. |
| SIN | Sine of 8-bit value. Result is in the range of +-127, unit circle is 0-255 radial units. |

Examples:

sin bytevar

BASIC Stamp II

```
sqr 50000  
~ in0
```

Binary operators take two terms and go between variables, constants, or expressions. They are as follows:

| | |
|-----|---|
| & | Bitwise AND |
| | Bitwise OR |
| ^ | Bitwise XOR |
| MIN | Limit value to minimum |
| MAX | Limit value to maximum |
| + | Addition |
| - | Subtraction |
| * | Multiply |
| ** | Multiply and return high 16-bits of result |
| */ | Multiply and return middle 16-bits of result (use to simultaneously multiply by a whole and a part; ie. 'value */ \$0180' multiplies by 1 and a half) |
| / | Divide |
| // | Divide and return remainder |
| DIG | Return decimal digit; '12345 dig 3' returns 2 |
| << | Shift left |
| >> | Shift right |
| REV | Reverse order of bits, lsb-justified; '%100110 rev 6' yields %011001 |

Examples:

```
ypos * xsize + xpos  
randword // 20  
countacc min 200 - 200 / 200
```

Parentheses can be placed to special-order the pattern of expression resolution. Though unary operators have highest priority and binary operators have secondary priority, and with those rules expressions

BASIC Stamp II

are resolved left-to-right, parentheses can override priority:

$X+1*Y-1$ 'something's wrong here if we need $(X+1)*(Y-1)$

$(X+1)*(Y-1)$ 'do it right

Up to 8 levels of parentheses can be used.

For use within conditional expressions (IF), there is a special unary operator and several binary operators. These conditional operators have highest priority of all.

NOT Highest priority unary

AND, OR, XOR Highest priority binaries

Note: These are arithmetically identical to expression operators:

~

&

|

^

though they differ in application.

Lower-priority conditional binary operators (still higher than expression ops):

< Less than

<= Less than or equal to

= Equal to

=> Equal to or greater than

> Greater than

<> Not equal

Note: These comparison operators return 0 for false and \$FFFF for true. Combined with NOT, AND, OR, and XOR, complex tests can be done.

To summarize, here are some examples:

outs = ~ dcd nibarray(index) 'lookup a nibble, decode it, not it

IF x<1 or not y>3 and (z=0 xor r=3) then loopback

BASIC Stamp II

BRANCH

Branch according to an index.

usage: BRANCH index,[label0,label1,label2,...labelN]

If *index=0*, a GOTO label0 will be executed. If *index=1*, a GOTO label1 will be executed. If the index exceeds the number of label entries, no branch will occur and execution will proceed at the next instruction.

BASIC Stamp II

BUTTON

Debounce button, auto-repeat, and branch if button is in target state.

usage: **BUTTON** pin,downstate,delay,rate,bytevariable,targetstate,label

Pin will be placed in input mode.

Downstate is the state which is read when the button is pressed.

Delay specifies down-time before auto-repeat in **BUTTON** cycles.

Rate specifies the auto-repeat rate in **BUTTON** cycles.

Bytevariable is workspace for the **BUTTON** instruction. It must be cleared to 0 before being used by **BUTTON** for the first time.

Targetstate specifies what state (0=not pressed, 1=pressed) the button should be in for a branch to occur.

Label specifies where to go if the button is in the target state.

*Please refer to the Stamp I manual for an in-depth description of the **BUTTON** instruction.*

BASIC Stamp II

COUNT

Count cycles on a pin for some milliseconds.

usage: COUNT pin,period,wordvariable

*Pin will be placed in input mode. For *period* milliseconds, cycles will be counted on the designated I/O pin. Both sides of the waveform must be at least 4 μ s in duration, which limits the input frequency to 125-kHz (assuming a 50/50 duty cycle). The result (0-65535) will be written into *wordvariable*.*

Note that a word variable (16 bits) must be used to count above 255. If you only need values between 0-255, then a byte variable will work.

BASIC Stamp II

DEBUG outputdata

Show variables and messages for debugging purposes.

usage: DEBUG "Here we are!" Show message when executed

When executed, the data after **DEBUG** will be sent to the PC for display. **DEBUG** data can be displayed in several modes. Straight data can be relayed to the PC, or you can have values printed in decimal, hex, binary, or ASCII. In the number-printing modes, the result of an expression can be printed or a complete relation can be shown between the expression and its result. For example:

DEBUG dec? X Show X in decimal with relation

will yield (if x=1):

X = 1

DEBUG dec X Show X in decimal

yields:

1

When printing numbers, these prefixes can be used before expressions:

| | | |
|-------------|-----------|--|
| ASC? | | Show ASCII value with relation |
| STR | bytevar | Output string from byte array - until 0 |
| STR | bytevar\n | Output string from byte array - n bytes |
| REP | value\n | Output value n times |
| DEC | value | Print value in decimal |
| DEC1-DEC5 | value | Print value in decimal - 1-5 digits |
| SDEC | value | Print value in signed decimal |
| SDEC1-SDEC5 | value | Print value in signed decimal - 1-5 digits |
| HEX | value | Print value in hex |
| HEX1-HEX4 | value | Print value in hex - 1-4 digits |
| SHEX | value | Print value in signed hex |
| SHEX1-SHEX4 | value | Print value in signed hex - 1-4 digits |
| IHEX | value | Print value in hex w/ '\$' |
| IHEX1-IHEX4 | value | Print value in hex w/ '\$' - 1-4 digits |

BASIC Stamp II

| | | |
|----------------|-------|--|
| ISHEX | value | Print value in signed hex w/'\$' |
| ISHEX1-ISHEx4 | value | Print value in signed hex w/'\$' - 1-4 digits |
| BIN | value | Print value in binary |
| BIN1-BIN4 | value | Print value in binary - 1-4 digits |
| SBIN | value | Print value in signed binary |
| SBIN1-SBIN16 | value | Print value in signed binary - 1-4 digits |
| IBIN | value | Print value in binary w/'%' |
| IBIN1-IBIN16 | value | Print value in binary w/'%' - 1-4 digits |
| ISBIN | value | Print value in signed binary w/'%' |
| ISBIN1-ISBIN16 | value | Print value in signed binary w/'%' -1-4 digits |

REP cannot be followed by a '?', but ASC needs one.

DEBUG statements can contain many strings and numbers, separated by commas. In addition, there are several special control characters which are interpreted by the PC:

| Name | Value | Effect |
|------|-------|--|
| CLS | 0 | Clears the screen and homes the cursor |
| HOME | 1 | Homes the cursor |
| BELL | 7 | Beep the PC speaker |
| BKSP | 8 | Backspace - backs up the cursor |
| TAB | 9 | Advances to the next 8th column |
| CR | 13 | Carriage return - down to next line |

Example program using DEBUG:

| | | | |
|--------|-------|--------------------------|--|
| count | var | byte | 'Define a byte variable called count |
| loop1: | debug | cls, bell | 'Clear the screen and beep the speaker |
| loop2: | debug | sdec? sin count | 'Show the signed-decimal sine of count |
| | | count = count + 1 | 'Increment count |
| | | if count <> 0 then loop2 | 'Loop until count rolls over |
| | pause | 1000 | 'Pause for 1 second |
| | goto | loop1 | 'Repeat the program |

BASIC Stamp II

DTMFOUT

Output DTMF tones.

usage: DTMFOUT pin,{ontime,offtime,}[key,key,key,...]

Pin will be temporarily placed in output mode for modulation. The default on and off times are 200 ms and 50 ms.

Ontime and *offtime* are optional overrides in milliseconds.

Key(s) are 0-15, which are the following tones:


0-9 are the digits 0-9

10 is *

11 is #

12-15 are A-D, which are fourth-column codes unavailable on normal telephones.

The pin may be filtered by an RC circuit to achieve a clean sine-wave. High-impedance speakers may be driven with a coupling cap and a filter cap (see below).



BASIC Stamp II

END

End program.

usage: END

Enter low-power mode and keep I/O's updated. Every ~2.3 seconds the I/O's will go high-z for ~18ms. Approximately 50µa average current will be consumed.

END is terminated only by a hardware reset.

BASIC Stamp II

FOR...NEXT

Establish a FOR...NEXT loop.

```
usage:   FOR variable = start TO end {STEP stepval}
         {some code}
         NEXT
```

STEP is for specifying a step value other than the default of 1; if specified, stepval must be positive since whether to add or subtract stepval from variable is determined dynamically at run-time (this allows '10 TO 0' without specifying a negative STEP value.).

FOR...NEXT loops can be nested up to 16 deep.

Note: NEXT is stand-alone and implies the variable from the last FOR statement.

BASIC Stamp II

FREQOUT

Output a sine-wave(s) for some time.

usage: FREQOUT pin,milliseconds,freq1{,freq2}


Pin will be temporarily placed in output mode for modulation.

Milliseconds specifies how long to output the frequency(s).

Freq1 specifies the (first) frequency in 1Hz units (0-32768 Hz).

Freq2 is optional and specifies a second frequency.

The pin may be filtered by an RC circuit to achieve a clean sine-wave. High-impedance speakers may be driven with a coupling cap and a filter cap (see below).



BASIC Stamp II

GOSUB

Go to a subroutine (and then RETURN later).

usage: GOSUB *ledset*

The execution point is stored and then a branch to *ledset* occurs. When a RETURN is encountered (in *ledset*), execution continues at the instruction following the GOSUB.

GOSUB's may be nested up to 4 deep and you are allowed 255 of them in your program.

BASIC Stamp II

GOTO

Go to a new point in the program.

usage: GOTO joe

A branch to *joe* will occur, rather than execution continuing at the next instruction.

BASIC Stamp II

HIGH

Make a pin an output and have it output 1.

usage: HIGH pin

Pin is 0-15.

Make the pin an output, and change its output latch to 1.

BASIC Stamp II

IF...THEN

Branch conditionally.

usage: IF conditionalexpression THEN label
 ie. IF x=1 then redoit

If the result of conditionalexpression is not 0, execution will be continued at *label*. Otherwise, execution continues at the next instruction.

BASIC Stamp II

INPUT

Make a pin an input.

usage: INPUT pin

Pin is 0-15.

Make a pin an input. The pin's output latch is unaffected.

BASIC Stamp II

LOOKDOWN

Lookdown a value and return an index.

usage: LOOKDOWN value,??[value0,value1,value2,...valueN],variable

?? is a comparison operator: =,<>,>,<,<=,=> (= is the default).

A comparison is made between *value* and *value0*; if the result is true, 0 is written into *variable*. If that comparison was false, another comparison is made between *value* and *value1*; if the result is true, 1 is written into *variable*. This process continues until a true is yielded, at which time the index is written into *variable*, or until all entries are exhausted, in which case *variable* is unaffected.

BASIC Stamp II

LOOKUP

Lookup a variable according to an index.

usage: LOOKUP index,[value0,value1,value2,...valueN],variable

If *index=0*, then *value0* will be written to *variable*. If *index=1*, then *value1* will be written to *variable*. If the index exceeds the number of value entries, then *variable* will not be affected.

BASIC Stamp II

LOW

Make a pin an output and have it output 0.

usage: LOW pin

Pin is 0-15.

Make the pin an output, and change its output latch to 0.

BASIC Stamp II

NAP

Nap for a short period.

usage: NAP x

Enter low-power mode for a short period. When the period is over, the I/O's will go high-z for ~18ms and execution will continue at the next instruction.

The x values for NAP are as follows:

| x | ~seconds |
|---|----------|
| 0 | 0.018 |
| 1 | 0.036 |
| 2 | 0.072 |
| 3 | 0.140 |
| 4 | 0.290 |
| 5 | 0.580 |
| 6 | 1.200 |
| 7 | 2.300 |

BASIC Stamp II

OUTPUT

Make a pin an output.

usage: OUTPUT pin

Pin is 0-15.

The pin will be made an output. The pin's output latch is not affected.

BASIC Stamp II

PAUSE

Pause for x milliseconds (x=0 to 65535).

usage: PAUSE x

A delay of x milliseconds will occur.

BASIC Stamp II

PULSIN

Input a timed pulse.

usage: PULSIN pin,state,variable

Pin will be placed in input mode. A pulse of *state* will be awaited and measured with $2\mu\text{s}$ resolution, and the result will be written into *variable*.

If an overflow occurs while waiting for any edge, ($>65535*2\mu\text{s}$ or $>131\text{ms}$), 0 will be written into variable.

BASIC Stamp II

PULSOUT

Output a timed pulse.

usage: PULSOUT pin,period

*Pin will be made an output opposite of it's OUTx value for $period * 2\mu s$.*

Pin will be left in output mode with OUTx state.

Period may be a value from 0-65535; a value of 0 will result in no output pulse.

BASIC Stamp II

PWM

Pulse-width modulate a pin for some time.


usage: PWM pin,duty,cycles

Pin will be temporarily made an output while it is modulated.

Duty is an 8-bit value (0-255) which specifies the duty-cycle.

Cycles is the number of 256 pin update periods which take ~1ms. When done, *pin* will be placed in input mode to allow the voltage to remain until another PWM is executed.

A digital-to-analog converter can be made by connecting the pin to a resistor which goes to a cap which goes to GND. The resistor-cap junction will reflect the duty (0-5V) during and after PWM (see below).



BASIC Stamp II

RANDOM

Pseudo-randomly iterate a word variable.

usage: RANDOM wordvariable

wordvariable will be iterated **16** times to potentially change every bit.

BASIC Stamp II

RCTIME

Measure an RC charge/discharge time.


usage: RCTIME pin,state,variable

Pin will be placed in input mode and time will be measured in 2 μ s units while *pin* is in *state*. The result will be written into *variable*. If an overflow occurs (>131ms), 0 will be written.

This is useful for measuring resistor-capacitor charge/discharge times. Since the logic threshold of a pin is ~1.4 volts, it is best to have the RC voltage go from the 5V supply towards ground, yielding a span of ~3.6 volts. For example, to convert a potentiometer setting to a number:

Connect the pot as shown below. Make the pin high for 1 ms, then do RCTIME. The resistor-cap junction will start at 5V and fall towards ground. When ~1.4 is reached, the counting will terminate and the result will be returned to *variable*. Adjusting the pot causes the returned value to go up or down.

Note: the 10-ohm resistor may be necessary to avoid a possible short between ground and the high I/O pin.



Sample Program:

Pot var word

```
Loop: HIGH 0                    'Discharge capacitor
      PAUSE 1                    'Allow time for discharge
      RCTIME 0,1,Pot            'Measure charge time
      DEBUG ?Pot                'Show result on PC
      GOTO loop                 'Repeat the process
```

BASIC Stamp II

READ

Read a byte from the EEPROM.

usage: READ location,variable

Location is 0-2047. Variable will receive the byte read from location.

BASIC Stamp II

RETURN

Return from a subroutine.

usage: RETURN

The execution point is set to the instruction after the GOSUB that got into the subroutine executing the RETURN.

If a RETURN is executed without a corresponding GOSUB, execution begins anew at the start of the program.

BASIC Stamp II

REVERSE

Reverse a pin's input/output direction.

usage: REVERSE pin

Pin is 0-15.

The pin will be changed from an input to an output, or from an output to an input. The state of its output latch is not affected.

BASIC Stamp II

SERIN *rpin*{*fpin*},*baudmode*,{*plabel*,}{*timeout*,*tlabel*,}{*inputdata*]
Input data serially.

example:

```
SERIN 4,32+$4000,60000,nothingcame,[WAIT (","),STR bytearray\16\,""]
```

Serial pin

Baudrate, etc.

Timeout delay

Jump to if timeout

Wait for comma

Receive 16 bytes

Accept serial data on pin 4. Reception mode is 19,200 baud, 8 data bits, no parity, inverted data. If no data is received after 60 seconds (60,000 milliseconds), execution will jump to *nothingcame*. If data is received, SERIN will wait for a comma (“,”) before accepting bytes. After the comma is received, up to 16 bytes will be received and placed into *bytearray*; if another comma is received before 16 bytes of data, then the remaining bytes in the array will be filled with 0’s.

Rpin is 0-15 for an I/O pin, or 16 for the internal serial port (pin 2, RX). If a regular I/O pin is used, then the input will be on a TTL-level pin. If the RX pin is used, then the input will be on a pseudo-RS232 pin. The difference is this:

On a TTL-level pin (0-15), the signals received are 0 to 5 volts. Serial communication with TTL signals should work well for most applications (certainly if the communicating devices are all TTL-level). *If a TTL pin is used to receive RS232-level signals, then the signal should pass through a 22K resistor before reaching the pin (otherwise, the TTL pin may be damaged).*

On the RS232-level pin (16), the signals received are -10 to 10 volts. Serial communication with RS232 signals is standard on most serial devices, such as printers, modems, etc. This pin is designed to accept RS232 signals, so no in-line resistor is necessary.

In either case, the low/high threshold is at 1.4 volts (anything below reads as 0, anything above reads as 1).

BASIC Stamp II

Special note: if the RS232 serial port (TX and RX) is used AND the Stamp II is connected to a PC via the normal serial programming cable AND the PC is running a terminal program, then you may experience odd behavior when trying to use the terminal program to communicate with the Stamp II. This is because many terminal programs hold the DTR line high, which is the same line used to reset the Stamp II prior to programming. If you are experiencing this problem, you should disconnect the DTR line (pin 3 on the Stamp II) when using the terminal program.

Fpin is an optional flow-control pin. This pin may be used to implement “flow-control” handshaking between serial devices.

Baudmode is a composite value which specifies baud rate, parity mode, and true/inverted input.

Bits 0-12 of *baudmode* are the serial bit period expressed in microseconds-20. Bit 13 (\$2000) is 0 for 8-bit no parity, 1 for 7-bit parity. Bit 14 (\$4000) is 0 for true, 1 for inverted. Bit 15 (\$8000) is not used for SERIN.

If the RS232-level pin (16) is specified, then *baudmode* bit 14 is ignored. However, it will still affect operation of the optional flow-control pin (*fpin*).

An easy formula for calculating the bit period (bits 0-12) is:

$$\text{int} \left(\frac{1,000,000}{\text{baud rate}} \right) - 20$$

Example values for *baudmode*:

| | |
|--------------|---|
| 3313 | 300 baud, 8-bit, no parity, true data |
| 3313 +\$2000 | 300 baud, 7-bit, parity, true data |
| 3313 +\$4000 | 300 baud, 8-bit, no parity, inverted data |
| 3313 +\$6000 | 300 baud, 7-bit, parity, inverted data |
| 813 | 1200 baud, 8-bit, no parity, true data |
| 396 | 2400 baud, 8-bit, no parity, true data |
| 188 | 4800 baud, 8-bit, no parity, true data |
| 84 +\$6000 | 9600 baud, 7-bit, parity, inverted data |
| 32 | 19200 baud, 8-bit, no parity, true data |
| 6 | 38400 baud, 8-bit, no parity, true data |

BASIC Stamp II

Label is an optional label that specifies where to branch in the event of a parity error (parity mode must be enabled).

Timeout is an optional value that specifies how long to wait before giving up and branching to *label*. The amount of time is measured in milliseconds, and may be up to 65535 (approximately 65 seconds).

Inputdata follows the conventions below:

| | |
|------------------------|---|
| variable | Input a byte and store in variable. |
| STR bytearrayL{E} | Input a string into bytearray of length L with optional end-character of E (0's will fill remaining bytes). |
| SKIP L | Input and ignore L bytes. |
| WAITSTR bytearray | Wait for bytearray string (bytearray is terminated by 0). |
| WAITSTR bytearrayL | Wait for bytearray string of length L. |
| WAIT (value,value,...) | Wait for up to a six-byte sequence. |
| DEC variable | Input decimal value. |
| DEC1-DEC5 variable | Input decimal value of fixed length. |
| SDEC variable | Input signed decimal value. |
| SDEC1-SDEC5 variable | Input signed decimal of fixed length. |
| HEX variable | Input hex value (i.e., "00F3"). |
| HEX1-HEX4 variable | Input hex value of fixed length. |
| SHEX variable | Input signed hex value. |
| SHEX1-SHEX4 variable | Input signed hex value of fixed length. |
| IHEX variable | Input indicated hex value (i.e., "\$00F3"). |
| IHEX1-IHEX4 variable | Input indicated hex value of fixed length. |
| ISHEX variable | Input signed indicated hex value. |
| ISHEX1-ISHEX4 variable | Input signed indicated hex value of fixed length. |
| BIN variable | Input binary value. |
| BIN1-BIN16 variable | Input binary value of fixed length. |

BASIC Stamp II

| | |
|-------------------------|--|
| SBIN variable | Input signed binary value. |
| SBIN1-SBIN16 variable | Input signed binary value of fixed length. |
| IBIN variable | Input indicated binary value (i.e., "%1101"). |
| IBIN1-IBIN16 variable | Input indicated binary value of fixed length. |
| ISBIN variable | Input signed indicated bin value. |
| ISBIN1-ISBIN16 variable | Input signed indicated bin value of fixed length. |

BASIC Stamp II

SEROUT tpin,baudmode,{pace,}[outputdata]

SEROUT tpin\fpin,baudmode,{timeout,tlabel,}[outputdata]

Output data serially.

example:

```
SEROUT 3,84+$4000,100,["The temperature is ",dec temp," degrees.",cr]
```

Serial pin

Baudrate, etc.

Byte pace

Send text

Send decimal value

Send text

Send cr*

* carriage
return

Send serial data on pin 3. Transmission mode is 9,600 baud, 8 data bits, no parity, inverted data, driven output. Transmitted bytes will be sent at the rate of one byte every 0.1 seconds (100 milliseconds). Sample output would look like this: "The temperature is 75 degrees."

Tpin is 0-15 for an I/O pin, or 16 for the internal serial port (pin 1, TX). If a regular I/O pin is used, then the output will be on a TTL-level pin. If the TX pin is used, then the output will be on a pseudo-RS232 pin. The difference is this:

On a TTL-level pin (0-15), the signals sent are 0 to 5 volts. Serial communication with TTL signals should work well for most applications (certainly if the communicating devices are all TTL-level). *However, if the device receiving serial data requires real RS232 voltages, then it may not accept data from a TTL pin on the Stamp II.*

On the RS232-level pin (16), the signals sent are RX to 5 volts. This may seem a bit confusing, but this is how the circuit works: for sending a low signal, the Stamp II reflects the "rest" (low) state of the RX pin, which is usually about -10 volts; for sending a high signal, the Stamp II uses 5 volts. This system only works if the serial device to which the Stamp II is connected has "real" +/- voltage generation circuitry. Real RS232 voltages are standard on most serial devices, such as PCs, printers, modems, etc.

BASIC Stamp II

Fpin is an optional flow-control pin. This pin may be used to implement “flow-control” handshaking between serial devices.

Baudmode is a composite value which specifies baud rate, parity mode, true/inverted output, and open/driven output.

Bits 0-12 of *baudmode* are the serial bit period expressed in microseconds-20. Bit 13 (\$2000) is 0 for 8-bit no parity, 1 for 7-bit parity. Bit 14 (\$4000) is 0 for true, 1 for inverted. Bit 15 (\$8000) is 0 for driven, 1 for open-drain/open-source.

If the RS232-level pin (16) is specified, then *baudmode* bits 14 and 15 are ignored. However, their settings will still affect operation of the optional flow-control pin (*fpin*).

An easy formula for calculating the bit period (bits 0-12) is:

$$\text{int} \left(\frac{1,000,000}{\text{baud rate}} \right) - 20$$

Example values for *baudmode*:

| | |
|--------------|--|
| 3313 | 300 baud, 8-bit, no parity, true data, driven output |
| 3313 +\$2000 | 300 baud, 7-bit, parity, true data, driven output |
| 3313 +\$4000 | 300 baud, 8-bit, no parity, inverted data, driven output |
| 3313 +\$6000 | 300 baud, 7-bit, parity, inverted data, driven output |
| 3313 +\$8000 | 300 baud, 8-bit, no parity, true data, open drain/source |
| 813 | 1200 baud, 8-bit, no parity, true data, driven output |
| 396 | 2400 baud, 8-bit, no parity, true data, driven output |
| 188 | 4800 baud, 8-bit, no parity, true data, driven output |
| 84 +\$6000 | 9600 baud, 7-bit, parity, inverted data, driven output |
| 32 | 19200 baud, 8-bit, no parity, true data, driven output |
| 32 +\$2000 | 19200 baud, 7-bit, parity, true data, driven output |
| 6 | 38400 baud, 8-bit, no parity, true data, driven output |

Pace is an optional value that specifies how long to wait between transmitted bytes. The amount of time is measured in milliseconds, and may be up to 65535 (approximately 65 seconds). A pace value may only be specified if flow-control is not being used.

Timeout is an optional value that specifies how long to wait before giving up and branching to *tlabel*. The amount of time is measured in

BASIC Stamp II

milliseconds, and may be up to 65535 (approximately 65 seconds). A timeout value and label are only applicable if flow-control is being used.

Outputdata follows the DEBUG formatting conventions. Please refer to the DEBUG description earlier in this manual.

BASIC Stamp II

SHIFTIN

Shift bits in synchronously.

usage: SHIFTIN *dpin*,*cpin*,*mode*,[*variable*{\bits},...]

Dpin is the data input.

Cpin is the clock output.

Mode is 0 for msb-first/pre-clock, 1 for lsb-first/pre-clock, 2 for msb-first/post-clock, or 3 for lsb-first/post-clock.

Variable receives the shifted-in data.

Bits is an optional bit count. Values from 1-16 can be given; 8 is the default.

The following symbols are defined for use with SHIFTIN:

| Symbol | Value |
|---------|-------|
| MSBPRES | 0 |
| LSBPRES | 1 |
| MSBPOST | 2 |
| LSBPOST | 3 |

BASIC Stamp II

SHIFTOUT

Shift bits out synchronously.

usage: SHIFTOUT dpin,cpin,mode,[data{\bits},...]

Dpin is the data output.

Cpin is the clock output.

Mode is 0 for lsb-first or 1 for msb-first.

Data is a value to be shifted out.

Bits is an optional bit count. Values from 1-16 can be given; 8 is the default.

The following symbols are defined for use with SHIFTOUT:

| <u>Symbol</u> | <u>Value</u> |
|---------------|--------------|
| LSBFIRST | 0 |
| MSBFIRST | 1 |

Data is shifted out at approximately 16 kbits per second.

BASIC Stamp II

SLEEP

Sleep for x seconds (x=0 to 65535).

usage: SLEEP x

Enter low-power mode and keep I/O's updated. Every ~2.3 seconds, the I/O's will go high-z for ~18ms. Approximately 50µa average current will be consumed.

When x seconds have been accrued in SLEEP mode, execution continues at the next instruction. Though the granularity of SLEEP is ~2.3 seconds, the error is within 1% over extended periods of time.

BASIC Stamp II

STOP

Stop execution.

usage: STOP

Execution is frozen, but low-power mode is not entered. This is like END, except that the I/O's never go high-z; they remain driven.

Hardware reset will end STOP.

BASIC Stamp II

TOGGLE

Make a pin an output and toggle its output state.

usage: TOGGLE pin

Pin is 0-15.

The pin will be made an output and its output state (0 or 1) will be toggled: output of 0 is changed to 1; output 1 is changed to 0.

BASIC Stamp II

WRITE

Write a byte into the EEPROM.

usage: WRITE location,byte

Location is 0-2047. Byte is 0-255. Byte will be written into location.

BASIC Stamp II

XOUT

Output X-10 powerline control codes to a PL513 or TW523 powerline interface module.

usage: XOUT mpin,zpin,[house\keyorcommand{\cycles,...}]

Mpin will be made a low output and is the modulation control.

Zpin will be made an input and is the zero-crossing detect.

House is the house code (0-15 is 'A'-'P').

Keyorcommand is a key (0-15 is '1'-'16') or command (see table below).

Cycles is an optional number which overrides the default of two; this should only be used with 'dim' and 'bright' commands.

| X-10 Command (symbol) | Value |
|-----------------------|--------|
| UNITON | %10010 |
| UNITOFF | %11010 |
| UNITSOFF | %11100 |
| LIGHTSON | %10100 |
| DIM | %11110 |
| BRIGHT | %10110 |

The following chart gives the wiring connections for connecting the Stamp II to a PL513 or TW523 powerline interface module.

| Powerline Interface Pin | Stamp II Pin |
|-------------------------|--------------|
| 1 | Zpin |
| 2 | GND |
| 3 | GND |
| 4 | Mpin |

Application note #1 gives a good description of the X-10 system, as well as how to use it with the Stamp II.